

TEDOM



CHP UNITS 60 Hz

Overview of manufactured types

Micro, Cento and Quanto line

NATURAL GAS

CHP Unit type	Electrical Output (kW)	Heat Output max.		Electrical Efficiency LHV (%)	Thermal Efficiency LHV (%)	Total Efficiency max. LHV (%)	Fuel Consumption (BTU/h)	Heat Rate (BTU/kWe)
		kW	BTU/h					
Micro 35* SP	35	72.2	246,000	30.9%	63.9%	94.8%	385,000	11,000
Micro 35* AP	35	69.9	238,000	32.0%	63.5%	95.5%	375,000	10,700
Micro 55*	55	99	340,000	34.1%	61.5%	95.8%	549,000	9,989
Cento 100*	99	173	592,000	32.5%	57.0%	89.5%	1,038,000	10,485
Cento 150*	146	226	771,000	35.5%	55.1%	90.6%	1,402,000	9,587
Cento 200	192	255	873,059	37.8%	50.5%	88.3%	1,729,773	9,009
Cento 285*	285	422	1,440,000	37.0%	54.8%	91.8%	2,624,000	9,207
Cento 375	375	483	1,648,000	39.0%	50.3%	89.3%	3,279,000	8,744
Cento 555	555	726	2,477,000	38.8%	50.7%	89.5%	4,886,000	8,804
Quanto 600	600	685	2,337,000	42.4%	48.4%	90.8%	6,415,000	10,692
Quanto 800	800	908	3,098,000	42.6%	48.3%	90.9%	6,790,000	8,489
Quanto 1200	1200	1312	4,477,000	43.4%	47.4%	90.8%	9,441,000	7,868
Quanto 1600	1560	1733	5,913,000	42.9%	47.7%	90.6%	12,390,000	7,942
Quanto 2000	2000	2179	7,435,000	43.4%	47.2%	90.6%	15,737,000	7,868

* Combustion with the stoichiometric air-fuel ratio

BIOGAS

CHP Unit type	Electrical Output (kW)	Heat Output max.		Electrical Efficiency LHV (%)	Thermal Efficiency LHV (%)	Total Efficiency max. LHV (%)	Fuel Consumption (BTU/h)	Heat Rate (BTU/kWe)
		kW	BTU/h					
Micro 35	27	50.4	171,000	32.0%	59.6%	91.6%	287,000	10,600
Cento 100	94	148	505,000	33.5%	52.8%	86.3%	955,400	10,164
Cento 150	140	214	732,000	34.2%	52.3%	86.5%	1,397,000	9,979
Cento 200	191	261	891,000	36.8%	50.4%	87.2%	1,766,000	9,247
Cento 375	375	480	1,637,000	39.2%	50.2%	89.4%	3,262,000	8,699
Cento 555	555	767	2,617,000	38.0%	52.6%	90.7%	4,975,000	8,964
Quanto 600	600	674	2,230,000	41.5%	46.6%	88.1%	4,934,000	8,223
Quanto 800	800	892	3,042,000	41.7%	46.5%	88.6%	6,544,000	8,180
Quanto 1200	1200	1299	4,431,000	42.8%	46.2%	89.0%	9,578,000	7,982
Quanto 1600	1560	1721	5,872,000	42.3%	46.6%	88.9%	12,584,000	8,066
Quanto 2000	2000	2162	7,376,000	42.7%	46.1%	88.8%	15,989,000	7,995

PROPANE

CHP Unit type	Electrical Output (kW)	Heat Output max.		Electrical Efficiency LHV (%)	Thermal Efficiency LHV (%)	Total Efficiency max. LHV (%)	Fuel Consumption (BTU/h)	Heat Rate (BTU/kWe)
		kW	BTU/h					
Micro 35	35	71.5	243,968	31.5%	64.4%	95.9%	379,000	10,821
Cento 100	98	181	617,651	31.2%	57.6%	88.8%	1,071,000	10,929
Cento 150	157	259	884,820	33.8%	55.8%	89.6%	1,584,000	10,092
Cento 200	168	275	938,665	34.0%	55.6%	89.6%	1,687,000	10,040
Quanto 800	535	691	2,358,000	39.6%	51.2%	90.8%	4,606,000	8,610
Quanto 1200	911	1102	3,760,000	41.0%	49.6%	90.6%	7,575,000	8,315
Quanto 1600	1161	1422	4,852,000	40.7%	49.8%	90.5%	9,738,000	8,388
Quanto 2000	1381	1701	5,804,000	40.5%	49.8%	90.3%	11,649,000	8,435

Issued 02/2019

Notes for data in all tables

Gas consumption is referenced for natural gas with heating value of 912.18 BTU/CF and at ambient conditions: 59 °F, 14.648 psi – with tolerance according – to ISO 3046-1. Gas consumption is referenced for biogas with methane volume 65% (629.4 BTU/CF), at normal conditions (32 °F, 14.648 psi). Biogas mark means fuels incurred by biological decomposition – e.g. gas from water treatment plants, agricultural concerns or communal landfill sites. Gas consumption is referenced for propane (acc. to DIN 51622) (2,498 BTU/CF). Parameters of Propane CHP units are calculated for ambient temperature 86 °F and humidity of 75%. Referenced data is for general purposes only. Consult with TEDOM factory or country area authorized TEDOM representative for specific application assistance. All rights reserved specifications subject to change. TEDOM is a registered trademark of TEDOM a.s. It is possible to combine more units in one container. Technical specifications of these units and their configuration are available on request.