

BIOGAS

basic technical data

CHP Unit type	Electrical Output (kW)	Heat Output (kW)	Electrical Efficiency (%)	Heat Efficiency (%)	Total Efficiency (%)	Power input in fuel (kW)
Micro 30	30	59	30.9	60.7	91.6	97.1
Cento 80	75	104	36.0	49.8	85.8	209
Cento 100	106	143	36.4	49.2	85.6	291
Cento 120	124	165	36.9	49.2	86.1	336
Cento 160	166	217	37.8	49.5	87.3	439
Cento 180	182	224	39.1	48.1	87.2	465
Cento 200	200	245	39.2	48.1	87.3	510
Cento 210	210	241	40.4	46.5	86.9	519
Flexi 250 ³	250	235	42.5	40.0	82.5	588
Flexi 265 ³	265	249	43.0	40.0	83.0	624
Cento 350	355	419	40.1	47.3	87.4	885
Cento 430	430	527	39.5	48.4	87.9	1 087
Cento 530	528	613	40.2	46.6	86.8	1 315
Quanto 600	600	639	42.9	45.6	88.5	1 400
Quanto 800	800	843	43.1	45.4	88.5	1 856
Quanto 1000	999	1 089	42.6	46.4	89.0	2 345
Quanto 1200	1 200	1 283	43.0	46.0	89.0	2 790
Quanto 1600	1 560	1 697	42.7	46.4	89.1	3 654
Quanto 2000	2 000	2 138	43.0	46.0	89.0	4 651

3. Product of TEDOM SCHNELL GmbH.

Issued 12/2019

Notes for data in all tables

Referenced data is for general purposes only.

The technical parameters apply to emission standards according to the European legislation, which defines a maximum of 250 mg NO_x/Nm³ for cogeneration units over 1 MW in fuel input. The specified NO_x and CO emission level apply at a concentration of 5% O₂ in the dry flue gas. Gas consumption is referenced with tolerance according to ISO 3046-1.

The term biogas also includes other fuels resulting from biological decomposition - such as sewage or landfill gas.

These parameters may vary with respect to technical and design developments or innovations. TEDOM reserves the right to make changes.

TEDOM



CHP UNITS

Overview of manufactured types

NATURAL GAS

basic technical data

CHP Unit type	Electrical Output (kW)	Heat Output (kW)		Electrical Efficiency (%)	Heat Efficiency (%)		Total Efficiency (%)		Emission NOx/CO (mg/Nm ³)
		standard / increased ¹			standard / increased ¹		standard / increased ¹		
Micro 20	20	41.8	47.2	30.7	64.1	72.4	94.8	103.1	95 / 300
Micro 30	30	58.1	65.4	32.4	62.8	70.7	95.2	103.1	95 / 300
Micro 33	33	63.7	71.8	32.5	62.8	70.7	95.3	103.2	95 / 300
Micro 50	50	88.5	101.5	34.2	60.6	69.5	94.8	103.7	95 / 300
Cento 80	81	120	126	35.1	52.2	54.5	87.3	89.6	500 / 650
Cento 100	104	142	149	36.9	50.5	52.9	87.4	89.8	500 / 650
Cento 120	125	177	185	36.4	51.7	54.0	88.1	90.4	500 / 650
Cento 130	133	191	196	37.8	54.2	55.7	92.0	93.5	95 / 300
Cento 160	164	221	231	37.8	50.9	53.3	88.7	91.1	500 / 650
Cento 180	184	232	243	39.2	49.5	51.8	88.7	91.0	500 / 650
Cento 200	200	253	265	39.2	49.5	51.9	88.7	91.1	500 / 650
Cento 210	210	267	279	39.7	50.5	52.7	90.2	92.4	500 / 300
Cento 260	260	371	382	37.8	54.0	55.5	91.8	93.3	95 / 300
Cento 350	355	442	457	40.0	49.8	51.5	89.8	91.5	500 / 300
Cento 430	430	609	640	37.0	52.5	55.2	89.5	92.2	250 / 300
Cento 530	528	672	705	39.3	50.0	52.4	89.3	91.7	250 / 300
Quanto 600	600	690	726	42.0	48.3	50.9	90.3	92.9	250 / 300
Quanto 800	800	911	959	42.3	48.2	50.8	90.5	93.1	250 / 300
Quanto 1000	999	1 155	1 216	42.0	48.5	51.1	90.5	93.1	250 / 300
Quanto 1200	1 200	1 355	1 428	42.6	48.1	50.7	90.7	93.3	250 / 300
Quanto 1600	1 560	1 788	1 884	42.2	48.4	51.0	90.6	93.2	250 / 300
Quanto 2000	2 000	2 251	2 372	42.6	48.0	50.6	90.6	93.2	250 / 300
Quanto 3000	3 333	3 577	3 740	43.6	46.8	48.9	90.4	92.5	250 / 300
Quanto 4000	4 500	4 679	4 904	44.3	46.0	48.3	90.3	92.6	250 / 300

NATURAL GAS

basic technical data for low emission design

CHP Unit type	Electrical Output (kW)	Heat Output (kW)		Electrical Efficiency (%)	Heat Efficiency (%)		Total Efficiency (%)		Emission NOx/CO (mg/Nm ³)
		standard / increased ¹			standard / increased ¹		standard / increased ¹		
Micro 20	20	41.8	47.2	30.7	64.1	72.4	94.8	103.1	50 / 150
Micro 30	30	58.1	65.4	32.4	62.8	70.7	95.2	103.1	50 / 150
Micro 33	33	63.7	71.8	32.5	62.8	70.7	95.3	103.2	50 / 150
Micro 50	50	88.5	101.5	34.2	60.6	69.5	94.8	103.7	50 / 150
Cento 80	85	141	145	33.7	56.1	57.7	89.8	91.4	50 / 150
Cento 100	104	166	170	34.7	55.3	56.8	90.0	91.5	50 / 150
Cento 120	124	182	187	36.6	53.6	55.2	90.2	91.8	50 / 150
Cento 130	133	191	196	37.8	54.2	55.7	92.0	93.5	50 / 150
Cento 200	200	253	265	39.2	49.5	51.9	88.7	91.1	50 / 300 ²
Cento 210	210	267	279	39.7	50.5	52.7	90.2	92.4	50 / 300 ²
Cento 260	260	371	382	37.8	54.0	55.5	91.8	93.3	50 / 150
Cento 350	355	442	457	40.0	49.8	51.5	89.8	91.5	50 / 300 ²
Cento 430	430	544	570	39.7	50.2	52.6	89.9	92.3	50 / 300 ²
Cento 530	528	643	674	40.4	49.2	51.6	89.6	92.0	50 / 300 ²
Quanto 600	600	662	697	43.0	47.5	49.9	90.5	92.9	50 / 300 ²
Quanto 800	800	873	919	43.4	47.3	49.8	90.7	93.2	50 / 300 ²
Quanto 1000	999	1 107	1 165	43.0	47.6	50.1	90.6	93.1	50 / 300 ²
Quanto 1200	1 200	1 295	1 364	43.7	47.1	49.6	90.8	93.3	50 / 300 ²
Quanto 1600	1 560	1 709	1 797	43.3	47.5	49.9	90.8	93.2	50 / 300 ²
Quanto 2000	2 000	2 155	2 271	43.7	47.1	49.6	90.8	93.3	50 / 300 ²
Quanto 3000	3 333	3 577	3 767	43.6	46.8	49.2	90.4	92.8	50 / 300 ²
Quanto 4000	4 500	4 679	4 941	44.3	46.0	48.6	90.3	92.9	50 / 300 ²

We also offer cogeneration units with different emission levels. Technical parameters of these CHP units are available on request.

1. With additional exhaust heat exchanger.
2. With SCR technology.